



CM75

Finn-Power CM75 hose-cutting machine has been designed to cut up to 2" diameter 6-spiral hoses. The hose is pushed against the blade by a pneumatic pusher.

Pusher movement speed can be quickly and easily adjusted to choose optimal cutting speed for every hose. The blade can be sharpened when necessary. The cutter has a built-in bin for collecting cutting waste.

SAFE- and QT-models also available.

TTO INION DATA		
TECHNICAL DATA		
Max. hose size (inch)	2	
Diameter (blade) external (mm)	520x4	
Diameter (blade) internal (mm)	38	
Max. hose OD (mm)	71	
Exhaust outlet OD (mm)	103	
Motor Power (kW/HP)	7.5 / 10.0	
Velocity, 50Hz (rpm)	2840	
Velocity, 60Hz (rpm)	2840	
DIMENSIONS (LxWxH)		
mm	990x714x1318	
inch	39.0x28.2x51.9	
WEIGHT		
kg/lbs	300/485	



l when necessary.	STANDARD FEATURES
	Toothed blade (part no 12251)
	Foot pedal (part no 701405)
	Adjustable pneumatic pusher speed
	Adjustable hose support
	OPTIONS
	Measuring table (2 m segments) (part no 692091)
	Fume extractor (part no 691992)
	Smooth blade (part no 055201)
	Measuring table (left/right handed) as an option.