



CUTTING | PRODUCTION | CM75 SAFE



CM75 SAFE

Finn-Power CM75 SAFE has the same capacity as in CM75 with added safeguard and motor brake. Safeguard opens only after blade rotation has stopped.

Service free electrical brake stops the blade in only 3 seconds.

Pusher movement speed can be quickly and easily adjusted to choose optimal cutting speed for every hose. The blade can be sharpened when necessary. The cutter has a built-in bin for collecting cutting waste.

See also QT-model.

ABSOLUTE
QUALITY
MADE IN
FINLAND

STANDARD FEATURES

- Toothed blade (part no 12251)
- Foot pedal
- Adjustable pneumatic pusher speed
- Adjustable hose support
- Safeguard
- Motor brake

OPTIONS

- Measuring table (2 m segments) (part no 692091)
- Fume extractor (part no 691992)
- Smooth blade (part no 055201)

TECHNICAL DATA


Max. hose size (inch)	2
Diameter (blade) external (mm)	520x4
Diameter (blade) internal (mm)	38
Max. hose OD (mm)	71
Exhaust outlet OD (mm)	103
Motor Power (kW/HP)	7.5 / 10.0
Velocity, 50Hz (rpm)	2840
Velocity, 60Hz (rpm)	2840

DIMENSIONS (LxWxH)

mm	990x890x1318
inch	39x35x51.9

WEIGHT

kg/lbs	340/748
--------	---------



Measuring table (left/right handed) as an option.